

Neptune Theatre Audio Specs

Head Audio Engineer:

Kristopher Couture - kboardc@gmail.com

Venue Policy: 104dba RMS limit

MAIN SPEAKER SYSTEM

Flown, stereo d&b audiotechnik Ci7 system with B2 subs powered with D6 & D12 amplifiers.

- 2 d&b Ci7 Top Loudspeaker Balcony – Main
- 2 d&b Ci7 Sub Loudspeaker Balcony - Sub
- 2 d&b Ci7 Top Loudspeaker Main Floor – Main
- 2 d&b B2 Sub Woofer Loudspeaker NL4 Main Floor – Sub
- 4 d&b Ci80 Loudspeaker Main Floor Fill & Under Balcony Fill
- 5 d&b D6 Amplifiers for Balcony & Main Floor Speakers
- 1 d&b D12 Amplifier Main Floor - Sub
- 1 R70 Ethernet to CAN Interface
- 2 EAW NT 59 FRONT FILL HI/MID CABINET
- 2 EAW NTS-22 FRONT FILL SUB WOOFER

FOH SYSTEM

Located Main Floor Center, 43' from Downstage Edge

- 1 Midas Pro2 Console System with DL251 Stage Rack 48 in x 16 out

MONITOR SYSEM

Located Stage Left Wing

- 1 Avid SC48 48 in x 16 out Digital Console with Std. pack lug in's

SPEAKERS

- 8 EAW Microwedge; 12" co-axial (passive)
- 1 RCF SUB-8003AS-MK2 Active Subwoofer

AMPS & PROCESSING

- 4 QSC PL236 monitor system amplifiers: 120watts into 4ohms

INPUT DEVICES

- 4 Shure Beta 58 Industry Standard Vocal Mic
- 4 Shure SM58 Industry Standard Vocal Mic
- 10 Shure SM57 Industry Standard Instrument Mic
- 1 Shure Beta 57 Instrument Mic
- 2 Sennheiser MD 421 Dynamic Mic
- 4 Sennheiser e904 Clip-On Mic
- 2 Sennheiser e906 Instrument Mic
- 1 Shure Beta 52 Kick Drum Mic
- 2 Shure Beta 91A kick Drum Mic
- 4 Shure Beta 98AMP/C Clamp-On Condenser Drum Mic
- 2 Shure Beta56 Instrument Mic
- 4 Shure KSM137 Condenser Mic
- 2 Shure KSM32 Large Diaphragm Condenser Mic
- 1 Audix D6 Dynamic Mic
- 1 Audix i5 Dynamic Mic
- 1 Telefunken M81 Dynamic vocal/instrument mic
- 6 Radial Pro DI Mono Passive Direct Box
- 4 Radial Pro2 DI Stereo Passive Direct Box

RF DEVICES

Up to four wireless mics may be used at one time, in any combination

- 2 Shure SM58 Handheld Wireless Mic
- 2 Shure Beta58 Handheld Wireless Mic
- 2 Countryman B3 Lavalier Mic
- 2 Shure UR4S+ RF Receiver
- 1 Shure UR4D+ RF Receiver

SNAKE

- 1 150' Ram Latch 150' 52 Channel Snake
- 1 Ramtech 48+4 Splitter Ram Latch 54, 48 Female XLR + 4 M+F XLR Split x 2 Ram Latch Out
- 1 Ramtech 30' Fan Out 30'. Ramtech xo25 > Male Fan Out (monitors)

POWER

- 100a 3phase power service. Cam-lock in with reversed ground and neutral. L21-30 available for tour power as well. The house uses approximately 20a per leg.